



United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

| APPLICATION NO. | F | ILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------------|------------------|----------------|-------------------------|---------------------|------------------|
| 09/667,050 | 7,050 09/21/2000 | | Zohar Bogin | 42390.P9415 8359 | |
| 8791 | 7590 | 03/13/2006 | EXAMINER | | INER |
| BLAKELY 12400 WILS | | OFF TAYLOR & 2 | MCLEAN MAYO, KIMBERLY N | | |
| SEVENTH I | | | ART UNIT | PAPER NUMBER | |
| LOS ANGE | LES, CA | 90025-1030 | 2187 | | |

DATE MAILED: 03/13/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

| | | Application No. | Applicant(s) | | | | |
|---|--|--|---|--|--|--|--|
| | | 09/667,050 | BOGIN ET AL. | | | | |
| | Office Action Summary | Examiner | Art Unit | | | | |
| | | Kimberly N. McLean-Mayo | 2187 | | | | |
| The MAILING DATE of this communication appears on the cover sheet with the correspondence address Period for Reply | | | | | | | |
| A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION. - Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filled after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication. - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b). | | | | | | | |
| Status | | | | | | | |
| 2a)☐ 3)☐ | Responsive to communication(s) filed on <u>21 Ju</u> This action is FINAL . 2b)⊠ This Since this application is in condition for allowar closed in accordance with the practice under E | action is non-final. nce except for formal matters, pro | | | | | |
| Disposition of Claims | | | | | | | |
| 4) Claim(s) 8,9,12-15,17,19-21 and 30-32 is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration. 5) Claim(s) is/are allowed. 6) Claim(s) 8,9,12-15,17,19-21 and 30-32 is/are rejected. 7) Claim(s) is/are objected to. 8) Claim(s) are subject to restriction and/or election requirement. | | | | | | | |
| Application Papers | | | | | | | |
| 10)□ 1 | The specification is objected to by the Examine The drawing(s) filed on is/are: a) acc Applicant may not request that any objection to the Replacement drawing sheet(s) including the correct The oath or declaration is objected to by the Ex | epted or b) objected to by the Education of the Education of the drawing of the d | e 37 CFR 1.85(a). ected to. See 37 CFR 1.121(d). | | | | |
| Priority under 35 U.S.C. § 119 | | | | | | | |
| 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some * c) None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. | | | | | | | |
| 2) Notice 3) Inform | (s) e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (PTO-948) eation Disclosure Statement(s) (PTO-1449 or PTO/SB/08) No(s)/Mail Date | 4) Interview Summary Paper No(s)/Mail Da 5) Notice of Informal P 6) Other: | (PTO-413) ate atent Application (PTO-152) | | | | |

Art Unit: 2187

DETAILED ACTION

1. In view of the Appeal Brief filed on June 21, 2005, PROSECUTION IS HEREBY REOPENED. A detailed action is set forth below.

To avoid abandonment of the application, appellant must exercise one of the following two options:

- (1) file a reply under 37 CFR 1.111 (if this Office action is non-final) or a reply under 37 CFR 1.113 (if this Office action is final); or,
 - (2) request reinstatement of the appeal.

If reinstatement of the appeal is requested, such request must be accompanied by a supplemental appeal brief, but no new amendments, affidavits (37 CFR 1.130, 1.131 or 1.132) or other evidence are permitted. See 37 CFR 1.193(b)(2).

Claim Rejections - 35 USC § 101

2. 35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

Claims 8-9, 12-13 and 30-32 are rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. The claimed features in claims 8 and 30 do not yield a tangible result. The aforementioned claims call for translating a first/third address to second/fourth address. However, the claims do not contain any substantial practical application for use of the translated addresses. The claims transform an address from one value to another, which is not by itself sufficient for establishing a claim eligible for patent protection. State

Street Bank & Trust Co. v. Signature Financial Group Inc., 149 F.3d 1368. The claimed

Art Unit: 2187

invention as a whole must accomplish a practical application and it must produce a useful, concrete and tangible result. *Id*.

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 8-9, 12-14 and 30-32 are rejected under 35 U.S.C. 103(a) as being unpatentable over Jeddeloh (USPN: 6,477,623) in view of Campbell (USPN: 6,526,459).

Regarding claim 8, Jeddeloh discloses using a conversion table (Figure 2, Reference 202) to translate a first address (untranslated address from the graphics controller) from a graphics controller (Figure 2, Reference 140) to a second address (translated first address) to a memory (C 6, L 17-24, L 36-50); and using the conversion table to translate a third address (untranslated address from the bus controller) from a bus controller (Figure 2, Reference 130) to a fourth address (translated third address) to the memory (C 6, L 17-24, L 36-50). Jeddeloh does not disclose the second address having a greater number of bits than the first address and the fourth address having a greater number of bits than the third address. However, Campbell teaches a conversion table (TLB; C 3, L 32-34) to translate a first address to a second address, wherein the second address has a greater number of bits than the first address (C 3, L 37-42). This feature taught by Campbell provides flexible address space allocation. Hence, it would have been

Art Unit: 2187

obvious to one of ordinary skill in the art to incorporate Campbell's teachings with the system taught by Jeddeloh for the desirable purpose of efficiency and flexibility.

Regarding claim 9, the system taught by Jeddeloh and Campbell discloses the conversion able to translate the third address including a translation lookaside buffer (Jeddeloh – C 6, L 25-35).

Regarding claims 12-14, Jeddeloh and Campbell disclose the conversion table including comparing a first portion (virtual/linear address excluding the offset) of the third address (virtual/linear address) with entries in a first table and if the first portion matches a particular one of the entries in the first table, combining a value (physical page number/address) associated with the particular one with a second portion (offset) of the third address to form the fourth address (physical address) (Figure 3, References 310, 312; C 7, L 9-18 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses (C 6, L 28-30) and thus TLBs function such that the virtual/linear address, [excluding the offset], is compared to the addresses in the TLB and when a match is found, a physical address is formed by combining the physical page number [translated address] with the offset of the virtual/linear address and thus it is evident that these steps are performed when performing steps 310 and 312 in Figure 3), and if the first portion does not match any of the entries in the first table, referring to a second table (comprehensive table) to translate the third address (Jeddeloh; C 6, L 30-34; C 7, L 12-15), wherein the comparing includes comparing the first portion of the third address with entries in the first table (GART table) in an input-output controller (Figure 2, Reference 102) and

Art Unit: 2187

wherein the referring to the second table includes referring to the second table (comprehensive table) in main memory (system memory)(C 6, L 30-34; C 7, L 12-15).

Regarding claims 30-31, Jeddeloh discloses an address translator (Figure 2, comprised of References, 124 and 202, [the translation table stored in GART]) having a first interface to couple to a memory controller (signal line(s) within Reference 124 coupled to Reference 122), a second interface to couple to a graphics controller (signal line(s) within Reference 124 coupled to Reference 140), a third interface to couple to a bus controller (signal line(s) within Reference 124 coupled to Reference 130) and a table of entries, each entry having a first portion and a second portion (Figure 2, Reference 202; table stored within GART); a translation control circuit coupled to the address translator to program the entries in the address translator (the address translator comprises interfaces and a table, wherein neither of these elements have logic to control the operation of the address translator and thus it is evident that logic is coupled to the address translator for controlling its operations such as storing/programming addresses/entries in the table); wherein the address translator is to translate an address on the third interface into a first address on the first interface and to translate an address on the second interface into a second address on the first interface (C 6, L 36-50 - Jeddeloh discloses that addresses are received from any of the elements coupled to Reference 124 in Figure 2, and are translated using the table in the GART as long as the address falls within a reserved range of addresses). Jeddeloh does not disclose the address translator translating an address on the third interface into a first address on the first interface having a greater number of bits than the address on the third

Art Unit: 2187

interface nor translating an address on the second interface into a second address on the first interface having a greater number of bits than the address on the second interface. However, Campbell teaches the concept of an address translator translating an initial address into a first address, wherein the first address has a greater number of bits than the initial address (C 3, L 37-42). This feature taught by Campbell provides flexible address space allocation. Hence, it would have been obvious to one of ordinary skill in the art to incorporate Campbell's teachings with the system taught by Jeddeloh for the desirable purpose of efficiency and flexibility.

Regarding claim 32, Jeddeloh and Campbell disclose the address translator comprising a graphics translation lookaside buffer (Figure 2, Reference 202 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses [C 6, L 28-30]).

5. Claims 15, 17 and 19-21 are rejected under 35 U.S.C. 103(a) as being unpatentable over Jeddeloh (USPN: 6,477,623) in view of Campbell (USPN: 6,256,459) and Bryg et al. (USPN: 5,060,137).

Regarding claim 15, Jeddeloh discloses an apparatus comprising a translation lookaside buffer (Figure 2, Reference 202 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses [C 6, L 28-30]); control logic coupled to the translation lookaside buffer (hardware/software responsible for controlling Reference 202), wherein the control logic is to compare a first portion (virtual/linear address excluding the offset) of an initial address from a bus controller (virtual/linear address from bus controller, Reference 130 in Figure 2) with entries in the translation lookaside buffer and if a first matching entry is found, to

Art Unit: 2187

combine a first value (physical page number/address) associated with the matching entry with a second portion (offset) of the initial address to form a first translated address (physical address) (Figure 3, References 310, 312; C 7, L 9-18 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses (C 6, L 28-30) and thus TLBs function such that a virtual/linear address, [excluding the offset], is compared to the addresses in the TLB and when a match is found, a physical address is formed by combining the physical page number [translated address] with the offset of the virtual/linear address and thus it is evident that these steps are performed when performing steps 310 and 312 in Figure 3); wherein the control logic is further to access a table (comprehensive table) in memory if the matching entry is not found (C 6, L 30-34, C 7, L 12-15), find a second value (physical page number/address) in the table associated with the first portion, combine the second value with the second portion to form a second translated address (a physical address is formed by combining the physical page number with the offset of the initial virtual/linear address). Jeddeloh does not disclose the first translated address having a greater number of bits than the initial address, the second translated address having a greater number of bits than the initial address, an input register and an output register coupled to the TLB and to the control logic, wherein the control logic is to compare a portion of an initial address in the input register with entries in the TLB and holding a first translated address in the output register and holding a second translated address in the output register. However, Campbell discloses using a TLB to translate a first address into a second address, wherein the second address has greater bits than the first address (C 3, L 37-42). This feature taught by Campbell provides flexible address space allocation. Hence, it would have been obvious to one of ordinary skill in the art to incorporate Campbell's teachings with the system

Art Unit: 2187

taught by Jeddeloh for the desirable purpose of efficiency and flexibility. Campbell does not disclose the explicit details of the TLB, however, Bryg teaches a TLB (Figure 2) coupled to an input register (Figure 2, Reference 1; C 3, L 29-30) and an output register (Figure 3, Reference 31; C 3, L 65-67) and control logic (software or hardware logic for controlling the operation of the TLB), wherein the control logic is to compare an initial address in the input register with the entries in the TLB (C 3, L 43-61) and wherein a translated address is held in the output register (Figure, 2, PHYSICAL ADDRESS TO CACHE; C 3, L 65-67; Figure 3, PHYSICAL ADDRESS). It is well known in the art to store data/addresses in a register for the purpose of reducing jitter and glitches from the signals thereby providing accurate and stable data outputs. Jeddeloh addresses are not disclosed as stored in registers and thus are vulnerable to the effects of glitches and jitter. Hence, it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the teachings of Campbell and Bryg with the teachings of Jeddeloh for the desirable purpose of expanding the address capability of a system by allowing the system to access a larger amount of physical memory and thereby improving the performance of the system and for the desirable purpose of providing stability and accuracy.

Regarding claim 17, Jeddeloh, Campbell and Bryg disclose the control logic including logic for first and second control flows, wherein the second control flow is to translate an initial graphics controller address and does not access the table (Jeddeloh – C 7, L 9-12; the control logic responsible for translating an address using the GART, when a GART hit occurs) and wherein the first control flow is to translate an initial bus controller address and accesses the table

Art Unit: 2187

(Jeddeloh – C 7, L 12- 15; the control logic responsible for translating an address using the comprehensive table in system memory – when a GART miss occurs).

Regarding claim 19, Jeddeloh discloses a processor (Figure 1, Reference 116); a memory (Figure 1, Reference 104); a graphics controller (Figure 1, Reference 140); a bus controller (Figure 1, Reference 118); an input-output controller coupled to the processor, memory, graphics controller and bus controller (Figure 2, input-output controller is comprised of References 122, 124, 130, 202, 126, and 204), the input-output controller including a translation lookaside buffer (TLB)(Figure 2, Reference 202 -Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses [C 6, L 28-30]); control logic coupled to the translation lookaside buffer (hardware/software responsible for controlling Reference 202); wherein the control logic is to compare a first portion (virtual/linear address excluding the offset) of a first initial address (virtual/linear address) from the bus controller (via Reference 130) (C 6, L 36-50) with entries in the translation lookaside buffer and if a first matching entry is found, combining a first value (physical page number/address) associated with the first matching entry with a second portion (offset) of the first initial address to form a first translated address (physical address) (Figure 3, References 310, 312; C 7, L 9-18 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses (C 6, L 28-30) and thus TLBs function such that a virtual/linear address, [excluding the offset], is compared to the addresses in the TLB and when a match is found, a physical address is formed by combining the physical page number [translated address] with the offset of the virtual/linear address and thus it is evident that these steps are performed when performing steps 310 and 312 in Figure 3);

Art Unit: 2187

and wherein the control logic is further to compare a first portion of a second initial address from the graphics controller (Figure 2, Reference 140; C 6, L 36-50) with the entries in the translation lookaside buffer and if a second matching entry is found, to combine a second value (physical page/frame number) associated with the second matching entry with a second portion of the second initial address (offset portion) to form a second translated address (physical address) (Figure 3, References 310, 312; C 7, L 9-18 - Jeddeloh discloses that the GART table is a TLB for addresses in the reserved range of graphics addresses (C 6, L 28-30) and thus TLBs function such that the virtual/linear address, [excluding the offset], is compared to the addresses in the TLB and when a match is found, a physical address is formed by combining the physical page number [translated address] with the offset of the virtual/linear address and thus it is evident that these steps are performed when performing steps 310 and 312 in Figure 3. These same steps are performed for each address provided thereto from any of the elements coupled to Reference 124 in Figure 2 for translation). Jeddeloh does not teach the first translated address having more bits than the first initial address, the second translated address having more bits than the second initial address, an input register and an output register coupled to the TLB and control logic, wherein the control logic is to compare a first initial address in the input register with the entries in the TLB and a first translated address is held in the output register and wherein the control logic is to compare a second initial address in the input register with the entries in the TLB and a second translated address is held in the output register. However, Campbell discloses using a TLB to translate a first address into a second address, wherein the second address has greater bits than the first address (C 3, L 37-42). This feature taught by Campbell provides flexible address space allocation. Hence, it would have been obvious to one of ordinary skill in the art to

Art Unit: 2187

incorporate Campbell's teachings with the system taught by Jeddeloh for the desirable purpose of efficiency and flexibility. Campbell does not disclose the explicit details of the TLB, however, Bryg teaches a TLB (Figure 2) coupled to an input register (Figure 2, Reference 1, C 3, L 29-30) and an output register (Figure 3, Reference 31; C 3, L 65-67) and control logic (software or hardware logic for controlling the operation of the TLB), wherein the control logic is to compare an initial address in the input register with the entries in the TLB (C 3, L 43-61) and wherein a translated address is held in the output register (Figure, 2; PHYSICAL ADDRESS TO CACHE, C 3, L 65-67; Figure 3, PHYSICAL ADDRESS). It is well known in the art to store data/addresses in a register for the purpose of reducing jitter and glitches from the signals thereby providing accurate and stable data outputs. Jeddeloh addresses are not disclosed as stored in registers and thus are vulnerable to the effects of glitches and jitter. Hence, it would have been obvious to one of ordinary skill in the art at the time the invention was made to couple Jeddeloh's TLB to an input register and an output register, wherein a first initial address in the input register is compared with the entries in the TLB and a first translated address is held in the output register and wherein a second initial address in the input register is compared with the entries in the TLB and a second translated address is held in the output register for the desirable purpose of stability and accuracy.

Regarding claim 20, Jeddeloh, Campbell and Bryg disclose the control logic is further configured to access a table (comprehensive table) in memory if the first matching entry is not found (comprehensive table) to translate the third address (Jeddeloh - C 6, L 30-34; C 7, L 12-15), find a third value (physical page/frame number) in the table associated with the first portion

Art Unit: 2187

of the first initial address, combine the third value with the second portion of the first initial address to form a third translated address (Jeddeloh - Figure 3, References 310, 312 - the third value and the offset of the first initial address are combined to perform a memory operation and are thus combined to form a physical address) and hold the third translated address in the output register (Bryg).

Regarding claim 21, Jeddeloh, Campbell and Bryg disclose the control logic including logic for first and second control flows, wherein the second control flow is to translate an initial graphics controller address and does not access the table (Jeddeloh – C 7, L 9-12; the control logic responsible for translating an address using the GART, when a GART hit occurs) and wherein the first control flow is to translate an initial bus controller address and accesses the table (Jeddeloh – C 7, L 12- 15; the control logic responsible for translating an address using the comprehensive table in system memory – when a GART miss occurs).

Response to Arguments

6. Applicant's arguments with respect to the claims have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Kimberly N. McLean-Mayo whose telephone number is 571-272-4194. The examiner can normally be reached on Mon, Wed, Thurs (10-4), Tues (9:45 - 6:15).

Page 13

Application/Control Number: 09/667,050

Art Unit: 2187

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Donald Sparks can be reached on 571-272-4201. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

KIMBERLY MCLEAN-MAY PRIMARY EXAMINER Kimberly N. McLean-Mayo

Primary Examiner

Art Unit 2187

KNM

March 6, 2006

DONALD SPARKS SLIP**FR**VISORY PATENT EYAMI